

ProLite B2403WS | 24" Wide

The new iiyama flag ship 24" display is ideal for both the Home Enthusiast, Gamer and Business professional. The 1920 x 1200 pixel panel has the latest advancements in technology, boasting a 2000:1 Dynamic Contrast Ratio which can be disabled for greater colour accuracy and a 3msec response time ensuring the best possible video and animation playback with minimal blurring. Of course, the B2403 is HD Ready and incorporates the HDMI input for connectivity between DVD Players, Games Consoles and Graphics Cards choosing this interface type. A HDMI to DVI cable is now included as standard.



Technical data		
LCD Panel	Panel	TN
	Diagonal	24"
	Display area h x w	324 x 518.4 mm
	Response time	3 msec
	Contrast ratio	2000 : 1 DCR
	Brightness	300 cd / qm max
	Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 85°/75°
	Display colour	16.7 Million
	Pixel pitch h x v	0.270 x 0.270 mm
	Native resolution	2,3 MegaPixel (1920 x 1200)
Electronics	Horizontal sync	31-83 KHz
	Vertical sync	56-75 Hz
	Bandwidth	162 MHz
	Input connector	D-Sub, HDMI
Speaker		2 x 2W
Included accessories		power cable, D-Sub signal cable, audio cable, user manual, DVI-HDMI Cable
Apple - Mac		All iiyama monitors are compatible with Apple-Macintosh computers
Controls		On-Screen-Display in 10 languages (GB, F, D, I, ESP, PL, RU, JP, NL, Ch) and 6 Front controls(Auto, Exit/Volume Button, Scroll Down/Contrast Button, Scroll Up/Brightness Button, Menu/Select, Power)
User controls		brightness, contrast, colour adjust, auto adjust, geometry (horizontal/vertical position, pixel clock, phase), OSD language, OSD position, OSD time out, volume, input select, recall, miscellaneous (sharpness, DDC/CI, Display Information, DCR, OD, Display Mode)
Driver		Windows 95 / 98 / 2000 / ME / XP / Vista
Ergonomics		TCO'03, CE, MPR III (prEN50279), ISO13406-2
Safety		TÜV GS, FCC-B, UL/C-UL, VCCI-B, GOST-R
Power supply		AC 100-240V, 50/60 Hz
power supply unit		internal
Power usage		max. 65 W in normal use, max. 2 W in Power management mode
Power management		VESA DPMS, ENERGY STAR®
Mechanical	Anti-theft-device	Kensington-lock prepared
	VESA mounting	100 mm
	Height adjustment	130 mm
	Rotation (pivot function)	90°
	Swivel Stand	90°, each 45° right and left
	Tilt angle	20° up, 5° down
	Weight	8.7 kg
Dimensions w x h x d		566.0 x 445.0 (575.0) x 220.0 mm

All trademarks and registered trademarks acknowledged. E & O E. Specifications subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defaults.

Megapixel describes the size of your desktop and therefore the amount of information your display can show. A lcd with a physical resolution of 9.2 mega pixels (3840 x 2400) can show 6 times more information than a display with 1.3 mega pixels (1280 x 1024). That means your desktop is about 600 percent bigger.